

IVR 100/40-PP SC

IVR 100/40-Pp Sc: an industrial vacuum cleaner powered by compressed air for vacuuming dust or paste-like materials over long distances. With pocket filter.







Order no.

9.978-763.0

Technical data		
EAN code		4054278002064
Air flow	$l/s / m^3/h$	95 / 341
Vacuum	mbar / kPa	500 / 50
Container capacity	1	100
Rated input power	kW	4
Vacuuming type		Pneumatic
Connection nominal diameter		DN 50
Accessory nominal diameter		DN 50
Sound pressure level	dB(A)	55 - 80
Main filter dust class		М
Filter area for main filter	m²	1.75
Weight without accessories	kg	101
Weight incl. packaging	kg	104
Dimensions (L × W × H)	mm	915 × 760 × 1620

This machine requires instruction.

Equipment	
Container emptying	Set-down trolley
Included in the scope of supply.	

IVR 100/40-Pp Sc, 9.978-763.0, 2025-12-07

KARCHER





Low-dust emptying system with PE bag

- Low-dust emptying thanks to closing mechanism and pressure compensation hose.
- \blacksquare Simple and safe dust disposal thanks to PE bag.

Manual shaking mechanism for easy filter cleaning

 Regular operation of the shaking lever for constantly high suction power.

Low-noise operation

• Quiet operation thanks to sound-damped drive unit.

























		Order no.	Description	
ACCESORY SETS				
Accessory kit for solids/dust				
Accessory kit for solids/dust Expert DN 40	1	9.989-659.0	Accessory kit DN 40 for industrial vacuum cleaners (solids and dust): EVA hose (9.988-088.0), handle (9.977-679.0), standard nozzle (9.988-401.0), reducer (9.989-690.0).	
Accessory kit for solids/dust DN 50 Expert	2	9.989-662.0	Accessory kit DN 50 for industrial vacuum cleaners (solids and dust): EVA hose (9.988-090.0), handle (9.977-678.0), standard nozzle (9.988-402.0), reducer (9.977-772.0).	
NOZZLES				
Standard nozzles				
Standard PVC nozzle DN50	3	9.989-673.0	Electroconductive standard PVC nozzle. DN 50.	
Standard PVC nozzle DN70	4	9.989-676.0	Electroconductive standard PVC nozzle. DN 70.	
Standard nozzle silicone DN40	5	9.988-401.0	Stretchy standard nozzle made from silicone, inner cone DN 40.	
Standard nozzle silicone DN50	6	9.988-402.0		
Standard silicone nozzle DN70	7	9.989-672.0	Electroconductive standard silicone nozzle. DN 70.	
Standard nozzle cuttable rubber DN50	8	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	
Standard aluminium nozzle DN50	9	9.980-749.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 50.	
Standard aluminium nozzle DN70	10	9.989-663.0	Standard nozzle made from aluminium. Electroconductive. DN 70.	
Flexible standard nozzles				
Standard nozzle flexible PVC DN50	11	9.981-421.0	Electroconductive, flexible round nozzle made from galvanised steel, DN 50, with rubber mouthpiece DN 30.	
Standard nozzle flexible PVC DN70	12	9.981-422.0	Flexible, electroconductive standard nozzle, DN 70, with rubber mouthpiece.	
Standard nozzle, flexible, angled 90° PP DN50	13	9.981-430.0	Flexible, electroconductive angled nozzle, DN 50, length: 800 mm.	
Floor nozzles			<u>'</u>	
Aluminium floor nozzle 200 mm DN50	14	9.981-426.0	Floor nozzle, DN 50, with 200 mm suction width.	

 $[\]blacksquare$ Included in the scope of supply. \qed Available accessories.



















		Order no.	Description	
NOZZLES				
Floor nozzles				
Aluminium floor nozzle 370 mm DN50	15	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. DN 50.	
Aluminium floor nozzle, el, 370 mm, DN50	16	9.987-612.0	Electroconductive multi-purpose floor nozzle. 370 mm wide, DN 50.	
Aluminium floor nozzle 500 mm DN50	17	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	
Aluminium floor nozzle, el, 500 mm, DN50	18	9.981-925.0	Floor nozzle with 500 mm suction width and hinge. DN 50, electroconductive.	
Stainless steel floor nozzle el 370 mm DN50	19	9.988-115.0	Floor nozzle (370 mm) made from stainless steel, electroconductive, DN 50.	
Floor nozzle rubber strip oil-resistant. 220 mm	20	9.981-923.0	Squeegee with plastic strip for floor nozzle, 220 mm wide.	
Floor nozzle rubber strip 370 mm	21	9.981-914.0	Squeegee with profiled strip for floor nozzle, 370 mm wide.	
Floor nozzle rubber strip 500 mm	22	9.981-915.0	Oil-resistant squeegee with profiled strip for floor nozzle, 500 mm wide.	
Floor nozzle brush strip el. 370 mm	23	9.984-939.0	Electroconductive squeegee for floor nozzle, 370 mm wide.	
Floor nozzle brush strip 500 mm	24	9.980-764.0	Brush strip set for floor nozzle 500 mm, with profiled strip.	
Crevice nozzles		•		
Crevice nozzle PP 15 mm × 145 mm DN50	25	9.988-117.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 52.	
Crevice nozzle PU 22 mm × 175 mm DN50	26	9.981-482.0	Crevice nozzle made from PU, DN 50.	
Crevice nozzle 18 mm × 120 mm DN50	27	9.981-442.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 17 mm slot width.	
Crevice nozzle 25 mm × 120 mm DN50	28	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	

 $[\]blacksquare$ Included in the scope of supply. \qed Available accessories.





























				\neg
		Order no.	Description	
NOZZLES				
Crevice nozzles				
Crevice nozzle 28 mm × 120 mm DN70	29	9.981-444.0	Electroconductive crevice nozzle made from sheet steel, DN 70, with 30 mm slot width.	
Stainless steel crevice nozzle 22 mm × 220 mm DN 50	30	9.988-123.0	Stainless steel crevice nozzle, DN 50, suitable for use with food.	
Flexible crevice nozzles		'		
Flexible crevice nozzle silicone 65 mm DN50	31	9.988-403.0	Flexible crevice nozzle made from silicone, DN 50.	
Flexible crevice nozzle 11 mm × 58 mm DN40	32	9.989-681.0	Electroconductive and flexible crevice nozzle, 11 × 58 mm.	
Flexible crevice nozzle 12 mm × 45 mm DN50	33	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	
Flexible crevice nozzle 20 mm × 45 mm DN50	34	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	
Surface nozzles		'		
Silicone surface nozzle 120 mm DN50	35	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	
Aluminium surface nozzle 150 mm DN50	36	9.989-665.0	Surface nozzle, 150 mm, made from aluminium. DN 50.	
Liquid nozzles		<u>'</u>		
Liquid nozzle 900 mm DN50	37	9.981-427.0	Bypass nozzle, DN 50, overall length: 1000 mm.	
Borehole nozzles		<u>'</u>		
Blind hole nozzle DN40	38	9.989-671.0	90° curved blind hole nozzle with 60 mm diameter.	
Blind hose nozzle angled 60° DN40	39	9.989-669.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	
Blind hole nozzle angled 90° DN40	40	9.989-667.0	90° curved blind hole nozzle with 60 mm diameter. DN 40.	
Blind hose nozzle angled 90° 200 mm extension DN40	41	9.989-670.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	
BRUSHES				
Standard brushes				
Standard brush 40 mm DN50	42	9.981-432.0	Flat brush nozzle DN 50.	

 $[\]blacksquare$ Included in the scope of supply. \qed Available accessories.

















		Order no.	Description	
BRUSHES				
End brushes				
End brush Ø 82 mm DN50	43	9.989-608.0	Electroconductive end brush with 82 mm diameter. DN 50.	
Surface brushes				
Surface brush 300 mm DN50	44	9.981-912.0	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.	
HOSES				
PVC				
Hose PVC DN50 3 m	45	9.989-615.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 3 m.	
Hose PVC DN50 5 m	46	9.989-616.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 5 m.	
PVC hose DN50 15 m without connectors	47	9.989-634.0	PVC hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	
Hose PVC DN70 3 m	48	9.989-635.0	Electroconductive PVC hose, DN 70. Temperature-resistant up to 85 °C. Length: 3 m.	
Hose PVC DN70 5 m	49	9.989-643.0	PVC hose, DN 70. Temperature-resistant up to 85 °C and electroconductive. Length: 5 m.	
PVC hose DN70 15 m without connectors	50	9.989-636.0	PVC hose without tap adapter, DN 70. Electroconductive and temperature-resistant up to 85 $^{\circ}$ C. Length: 15 m.	
EVA hoses		•		
Hose EVA NW50 3 m	51	9.988-090.0	Electroconductive hose with NW50. Suitable for temperatures up to 65°C. Length: 3 m.	
Hose EVA NW50 5 m	52	9.988-091.0		
EVA hose DN50 15 m without connectors	53	9.989-631.0	EVA hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 65 $^{\circ}$ C. Length: 15 m.	
Hose EVA DN70 3 m	54	9.989-613.0	Electroconductive EVA hose, DN 70. Temperature-resistant up to 65 °C. Length: 3 m.	
Hose EVA DN70 5 m	55	9.989-624.0	Electroconductive EVA hose, DN 70. Temperature-resistant up to 65 °C. Length: 5 m.	
EVA hose DN70 15 m without connectors	56	9.989-632.0	EVA hose without tap adapter, DN 70. Electroconductive and temperature-resistant up to 65 $^{\circ}$ C. Length: 15 m.	

 $[\]blacksquare$ Included in the scope of supply. \qed Available accessories.













	_			_
		Order no.	Description	
HOSES		<u> </u>		
Hose installation sets				
Hose installation kit DN50	57	9.989-628.0	Multipiece hose connection kit, DN 50.	
Hose installation kit DN70	58	9.989-629.0	Multipiece hose connection kit, DN 70.	
PU hoses		<u>'</u>		
Hose PU DN50 3 m	59	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	
Hose PU DN50 5 m	60	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	
PU hose DN50 15 m without connectors	61	9.989-638.0	PU hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	
Hose PU DN70 3 m	62	9.989-644.0	Oil-resistant, electroconductive PU hose, DN 70. Temperature-resistant up to 80 °C, suitable for abrasive suction media. Length: 3 m.	
Hose PU DN70 5 m	63	9.989-645.0	Oil-resistant, electroconductive PU hose, DN 70. Temperature-resistant up to 80 °C, suitable for abrasive suction media. Length: 5 m.	
PU hose DN70 15 m without connectors	64	9.989-639.0	PU hose without tap adapter, DN 70. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	
ME-PU-hoses		•		
Hose ME-PU DN50 3 m	65	9.989-623.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	
Hose ME-PU DN50 5 m	66	9.989-625.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	
ME-PU hose DN50 15 m without connectors	67	9.989-641.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	
Hose ME-PU DN70 3 m	68	9.989-646.0	Oil-resistant, electroconductive ME-PU hose, DN 70. Temperature-resistant up to 110 $^{\circ}$ C, suitable for abrasive suction media. Length: 3 m.	
Hose ME-PU DN70 5 m	69	9.989-648.0	Oil-resistant, electroconductive ME-PU hose, DN 70. Temperature-resistant up to 110 $^{\circ}$ C, suitable for abrasive suction media. Length: 5 m.	
ME-PU hose DN70 15 m without connectors	70	9.989-642.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 70. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	

 $[\]hfill \square$ Available accessories.























		1		\neg
		Order no.	Description	
HANDLES				
Elbow aluminium 45° DN40	71	9.989-544.0	45° curved handle made from aluminium, DN 40.	
Elbow aluminium 45° DN50	72	9.989-547.0	Handle with 45° bend. Made from aluminium, DN 50.	
Handle DN50, curved	73	9.977-678.0	Electroconductive and 45° curved handle made from stainless steel. Inner cone DN 50.	
Handle DN 70	74	9.977-677.0		
Stainless steel handle NW50	75	9.988-111.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 50.	
SUCTION TUBES		<u>'</u>		
Suction tube 850 mm DN 50	76	9.977-531.0	850 mm long extension tube made from steel. Electroconductive and with inner cone DN 50.	
Suction tube 850 mm DN 70	77	9.981-910.0	Electroconductive extension tube, internal cone DN 70, 850 mm total length.	
Aluminium suction tube 1500 mm NW40	78	9.989-038.0	Aluminium extension tube, electroconductive, NW 40. Length: 1500 mm.	
Aluminium suction tube 1500 mm NW50	79	9.989-035.0	Electrically conductive suction tube (1500 mm) made of aluminium with 50 mm diameter.	
Stainless steel suction tube 850 mm NW40	80	9.989-039.0	Stainless steel extension tube, electroconductive, NW 40. Length: 850 mm.	
Stainless steel suction tube 850 mm NW50	81	9.988-114.0	Electroconductive extension tube made from stainless steel. Inner cone NW 50.	
ADAPTERS / REDUCERS / DISTRIBUTORS				
Accessories adapter				
Adapter accessories DN 50 to DN 51	82	9.989-603.0	Steel adapter for connection of DN 50 to DN 51. Electroconductive.	
Adapter accessories DN 51 to DN 50	83	9.989-601.0	Steel adapter for connection of DN 51 to DN 50. Electroconductive.	
Adapter accessories DN50 to DN61	84	9.989-602.0	Steel adapter for connection of DN 50 to DN 61. Electroconductive.	

 $[\]hfill \square$ Available accessories.



















		Order no.	Description	
ADAPTERS / REDUCERS / DISTRIBUTORS				
Accessories adapter				
Adapter accessories DN 61 to DN 50	85	9.989-604.0	Steel adapter for connection of DN 61 to DN 50. Electroconductive.	
Reducers/expanders				
Reducer DN 70 to DN 50	86	9.977-772.0		
Reduction DN70 to DN40	87	9.989-690.0	Electroconductive steel reducer for reduction from DN 70 to DN 40.	
Reduction DN50 to DN40	88	9.981-231.0	Reducer from DN 50 to DN 40. Material: Steel. Electroconductive.	
Stainless steel reducer DN 70 to DN 50	89	9.989-712.0		
Stainless steel reducer DN 70 to DN 40	90	9.989-713.0		
Expander				
Expansion DN40 to DN50	91	9.981-936.0	Reducer from external cone DN 40 to internal cone DN 50. Material: Steel. Electroconductive.	
Expansion DN50 to DN70	92	9.981-921.0	Reducer from external cone DN 50 to internal cone DN 70. Material: Steel. Electroconductive.	
Distributor		•		
Y distributor DN 70 to DN 50	93	9.989-611.0	Electroconductive steel fitting, DN 70/DN 50 / DN 50.	
Y-piece fitting DN50 to DN40	94	9.981-149.0	Manifold, electroconductive, steel, DN 50/40/40.	
EMPTYING SUPPORTS				
Other emptying aids				
Emptying aid crane	95	9.980-832.0		
PRE-SEPARATORS				
Pre-separator				
Pre-separator Ef solid materials 100 DN70	96	9.982-238.0	Mobile pre-separator station with 100 l volume and discharge flap.	
Pre-separator dust 40 I DN40	97	9.989-687.0		
Pre-separator dust 60 I DN50	98	9.989-688.0		

 $^{\ \}square$ Available accessories.













		Order no.	Description	
PRE-SEPARATORS				
Pre-separator				
Pre-separator drum 200 l	99	9.989-685.0	Standard drum which complies with the ISO 15750-2 standard.	
Pre-separator lid		·		
Pre-separator cover Op liquids ø 517 mm DN70	100	9.981-666.0	Pre-separator cover DN 70. Suitable for containers with 517 mm diameter.	
Pre-separator cover Op liquids ø 575 mm DN70	101	9.981-662.0	Pre-separator cover DN 70 for 200 litre standard drum (9.989-685.0).	
Pre-separator cover solid materials ø 517 mm DN70	102	9.981-665.0	Pre-separator cover DN 70. Suitable for containers with 517 mm diameter.	
Pre-separator cover solid materials ø 575 mm DN70	103	9.981-661.0	Pre-separator cover DN 70 for 200 litre standard drum (9.989-685.0).	
ACCESSORIES STATIONARY				
IV pipelines				
IV pipe Ø 42.4 mm	104	9.980-451.0		
IV pipe Ø 60 mm	105	9.980-452.0	Robust steel pipe, 1 m in length and with a wall thickness of 2 mm. Made from high-quality lacquered steel.	
IV pipe Ø 75 mm	106	9.980-453.0		
IV pipe Ø 100 mm	107	9.980-455.0		
IV pipe elbow 30° Ø 60.3 mm	108	9.980-545.0		
IV pipe elbow 30° Ø 76.1 mm	109	9.980-546.0		
IV pipe elbow 30° Ø 101.6 mm	110	9.980-547.0		
IV pipe elbow 45° ø 60.3 mm	111	9.980-548.0		
IV pipe elbow 45° ø 76.1 mm	112	9.980-549.0		

[☐] Available accessories.











	_			_
		Order no.	Description	
ACCESSORIES STATIONARY				
IV pipelines				
IV pipe elbow 45° ø 101.6 mm	113	9.980-550.0		
IV pipe elbow 60° ø 60.3 mm	114	9.980-551.0		
IV pipe elbow 60° ø 76.1 mm	115	9.980-552.0		
IV pipe elbow 60° ø 60.3 mm	116	9.980-553.0		
IV pipe elbow 90° ø 42.4 mm	117	9.985-373.0	Pipe elbow, hardened, made from coated steel with 2.6 mm wall thickness and 90° bend.	
IV pipe elbow 90° ø 60.3 mm	118	9.980-554.0		
IV pipe elbow 90° ø 76.1 mm	119	9.980-555.0		
IV pipe elbow 90° ø 101.6 mm	120	9.980-556.0		
IV pipe reduction Ø 120 mm to 100 mm	121	9.981-335.0	Reducer, painted, made from steel with 2 mm wall thickness. For reduction from 120 to 100 mm diameter. Length: 350 mm.	
IV pipe reduction Ø 120 mm to 60 mm	122	9.981-337.0	Reducer, painted, made from steel with 2 mm wall thickness. For reduction from DN 120 to DN 70. Length: 350 mm.	
IV pipe reduction Ø 100 mm to 75 mm	123	9.981-334.0	Steel reducer with 2 mm wall thickness for reduction from 100 to 75 mm diameter. Length: 350 mm.	
IV pipe reduction Ø 100 mm to 60 mm	124	9.981-336.0	Steel reducer with 2 mm wall thickness for reduction from 100 to 60 mm diameter. Length: 350 mm.	
IV pipe reduction Ø 80 mm to 75 mm	125	9.980-494.0		
IV pipe reduction Ø 80 mm to 60 mm	126	9.980-493.0		

[☐] Available accessories.









	Order no.	Description	
127	9.981-333.0	Reducer, painted, made from steel with 2 mm wall thickness. For reduction from 75 to 60 mm diameter. Length: 350 mm.	
128	9.981-228.0		
129	9.981-127.0		
130	9.981-126.0		
131	9.981-124.0		
132	9.981-123.0		
133	9.981-258.0	Pipe branch, 600 mm long, made from steel with 30° bend and 2 mm wall thickness. Diameter: 60/60/42.4 mm.	
134	9.981-128.0		
135	9.981-125.0		
136	9.981-122.0		
137	9.981-259.0	Pipe branch, 600 mm long, made from steel with 30° bend and 2 mm wall thickness. Diameter: 42.4/42.4/42.4 mm.	
138	9.981-135.0		
139	9.981-134.0		
140	9.981-133.0		
	128 129 130 131 132 133 134 135 136 137 138	127 9.981-333.0 128 9.981-228.0 129 9.981-127.0 130 9.981-126.0 131 9.981-124.0 132 9.981-123.0 133 9.981-258.0 134 9.981-125.0 135 9.981-125.0 136 9.981-125.0 137 9.981-259.0 138 9.981-135.0	127 9.981-333.0 Reducer, painted, made from steel with 2 mm wall thickness. For reduction from 75 to 60 mm diameter. Length: 350 mm. 128 9.981-228.0

 $[\]hfill\square$ Available accessories.













		Order no.
ACCESSORIES STATIONARY		
IV pipelines		
IV pipe manifold Y-piece Ø 75 mm to 60 mm	141	9.981-132.0
IV pipe manifold Y-piece Ø 60 mm to 42 mm	142	9.981-131.0
IV pipe connectors/fastenings		
IV pipe coupling Ø 42.4 mm	143	9.980-445.0
IV pipe coupling Ø 60 mm	144	9.980-446.0
IV pipe coupling Ø 75 mm	145	9.980-447.0
IV pipe coupling Ø 100 mm	146	9.980-449.0
IV pipe clamp Ø 41 - 44 mm	147	9.980-463.0
IV pipe clamp Ø 60 - 63 mm	148	9.980-464.0
IV pipe clamp Ø 74 - 78 mm	149	9.980-465.0
IV pipe clamp Ø 99 - 103 mm	150	9.980-466.0
IV pipe clamp Ø 116 - 120 mm	151	9.980-467.0
IV pipe floor support	152	9.981-118.0
IV pipe on hose adapter, female Ø 42.2 to DN40	153	9.981-256.0
IV pipe on hose adapter, female Ø 60 to DN50	154	9.981-166.0

[☐] Available accessories.























	_			$\overline{}$
		Order no.	Description	
ACCESSORIES STATIONARY				
IV pipe connectors/fastenings				
IV pipe on hose adapter, female Ø 75 to DN70 $$	155	9.981-170.0		
IV pipe on hose adapter, male Ø 42.2 to DN40	156	9.981-257.0	Steel adapter with 2 mm wall thickness. For connecting pipe and hose, DN 40, to diameter 42.4 \times 2.0 mm.	
IV pipe on hose adapter, male Ø 60 to DN50	157	9.981-332.0	Steel reducer with 2 mm wall thickness. End piece with external cone DN 50 to diameter 60.0×2.0 mm.) 🗆
IV pipe on hose adapter, male Ø 75 to DN70	158	9.981-195.0		
Suction point accessories		•		
Suction point standard PVC nozzle DN40	159	9.981-454.0	Elastic nozzle DN 40 for jet cookers.	
Suction point standard PVC nozzle DN50	160	9.981-455.0	Elastic nozzle DN 50 for jet cookers.	
Suction point, standard brush DN40	161	9.981-436.0	Steel brush nozzle with 2.6 mm wall thickness for jet cookers, DN 40.	
Suction point nozzle holder	162	9.981-520.0	For mounting intended nozzle holders made from steel to a wall. Suitable for nozzles with DN 40, DN 50 and DN 70.	
Suction point nozzle holder with limit switch	163	9.982-111.0	Jet cookers with sensor, for wall mounting. Suitable for nozzles DN 40, DN 50 and DN 70.	
Suction point hose hanger with limit switch ø 60 mm	164	9.982-083.0	Hose holder with limit switch for fastening to pipelines with 60 mm diameter.	
Suction point hose hanger with limit switch ø 75 mm	165	9.982-092.0	Hose holder with limit switch for fastening to pipelines with 75 mm diameter.	
Suction point hose hanger with limit switch	166	9.982-093.0	Hose holder with limit switch for wall mounting.	
Suction point suction arm DN50 without hose	167	9.981-776.0	Swivel arm DN 50 with relevant wall mounting. Arm length: 2 m.	
Suction point suction arm DN70 without hose	168	9.981-775.0	Swivel arm DN 70 with relevant wall mounting. Arm length: 2 m.	

[☐] Available accessories.











		Order no.	Description			
ACCESSORIES STATIONARY						
Suction point accessories						
Suction point suction arm DN50 without hose	169	9.981-781.0	Swivel arm DN 50 with floor support (100 × 100 mm), arm length: 2 m.			
Suction point suction arm DN70 without hose	170	9.981-780.0	Swivel arm DN 70 with floor support (100 × 100 mm), arm length: 2 m.			
Suction point suction arm DN70	171	9.981-920.0	Suction arm DN 70 to DN 100, arm length: 2.5 m.			
Suction point suction arm DN100	172	9.983-121.0	Suction arm DN 100, arm length: 2.5 m. Suction head with 150 mm diameter.			
Suction point PVC hose DN40 3m	173	9.989-701.0				
Suction point PVC hose DN40 5m	174	9.989-702.0				
Suction point PVC hose DN50 3m	175	9.989-693.0				
Suction point PVC hose DN50 5m	176	9.989-694.0				
Suction point PVC hose DN70 3m	177	9.989-703.0				
Suction point PVC hose DN70 5m	178	9.989-704.0				
Suction point PU hose DN40 3m	179	9.989-705.0				
Suction point PU hose DN40 5m	180	9.989-706.0				
Suction point PU hose DN50 3m	181	9.989-695.0				
Suction point PU hose DN50 5m	182	9.989-696.0				

 $[\]hfill\square$ Available accessories.

















		Order no.	Description			
ACCESSORIES STATIONARY						
Suction point accessories						
Suction point PU hose DN70 3m	183	9.989-707.0				
Suction point PU hose DN70 5m	184	9.989-708.0				
Suction point ME-PU hose DN40 3m	185	9.989-697.0				
Suction point ME-PU hose DN40 5m	186	9.989-698.0				
Suction point ME-PU hose DN50 3m	187	9.989-699.0				
Suction point ME-PU hose DN50 5m	188	9.989-700.0				
Hose end piece, rotatable, female DN40	189	9.989-654.0	Rotatable hose end, DN 40, electrically conductive.			
Hose end piece, rotatable, female DN50	190	9.989-653.0	Rotatable hose end, DN 50, electroconductive.			
Hose end piece, rotatable, female DN70	191	9.989-652.0	Rotatable hose end, DN 70, electroconductive.			
Hose end piece, male DN40	192	9.981-142.0	Steel hose connection piece with 2 mm wall thickness and DN 40 external cone.			
Hose end piece, male DN50	193	9.980-472.0				
Hose end piece, male DN70	194	9.981-144.0	Steel hose connection piece with 2 mm wall thickness and DN 70 external cone.			
Hose end connector, female, stainless steel DN 40	195	9.989-716.0				
Hose end connector, female, stainless steel DN 50	196	9.989-714.0				

[☐] Available accessories.











		Order no.	Description			
ACCESSORIES STATIONARY						
Suction point accessories						
Hose end connector, male, stainless steel DN 40	197	9.989-717.0				
Hose end connector, male, stainless steel DN 50	198	9.989-715.0				
Hose installation kit DN40 without end pieces	199	9.981-563.0	Multi-part connection kit for hose connections in nominal width DN 40. The kit consists of two black hose sleeves and the corresponding pipe clamps.			
Hose installation kit DN50 without end pieces	200	9.981-561.0	Multi-part connection kit for hose connections in nominal width DN 50. The kit consists of two black hose sleeves and the corresponding pipe clamps.			
Hose installation kit DN70 without end pieces	201	9.981-562.0	Multi-part connection kit for hose connections in nominal width DN 70. The kit consists of two black hose sleeves and the corresponding pipe clamps.			

[☐] Available accessories.