

Printing date 07.11.2025 Version number 10 (replaces version 9)

Revision: 25.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: VehiclePro High-Pressure Wash RM 806
- · UFI: 5080-70Y0-S002-CKP1
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Restricted to professional users.



Keep away from children.

- · Application of the substance / the mixture High pressure cleaner
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Alfred Kärcher SE & Co. KG

Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden Tel.: +49-7195-14-0

Karcher Ltd

Unit 3 Redcow Retail Centre Robinhood Road, Ballymount Dublin 22 D22 PY03

Tel.: +353 1 409 7777

Internet: www.karcher.com

Further information obtainable from:

Regulatory Affairs
Tel.: +49-7195-14-0
productsafety.management.de@karcher.com

1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont

Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

For Hazardous Materials [or Dangerous Goods] Incidents

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

nage 21



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. Eve Dam. 1

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- Signal word Danger
- · Hazard-determining components of labelling:

sodium hydroxide

fatty alcohol ethoxylate

isotridecanolethoxylate + 8 EO

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. P310

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Cleaning agent

(Contd. on page 3)



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

Dangerous components:		
CAS: 15763-76-5 EINECS: 239-854-6 Reg.nr.: 01-2119489411-37-xxxx	sodium p-cumenesulphonate Eye Irrit. 2, H319	1-5%
CAS: 1310-73-2 EINECS: 215-185-5 Index number: 011-002-00-6 Reg.nr.: 01-2119457892-27-xxxx	sodium hydroxide Met. Corr.1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0.5 % ≤ C < 2 % Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	≥2-<3%
CAS: 78330-20-8	fatty alcohol ethoxylate Eye Dam. 1, H318; Acute Tox. 4, H302	≥1-<3%
CAS: 69011-36-5	isotridecanolethoxylate + 8 EO ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302	≥1-<3%
Regulation (EC) No 648/2004	on detergents / Labelling for contents	•
non-ionic surfactants, anionic surf	actants, polycarboxylates	<5%

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information Immediately remove any clothing soiled by the product.
- · After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- · After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed.
 No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 3)

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with eyes and skin.

- · Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility:

Do not store together with acids.

Keep away from food, beverages and feed.

- · Further information about storage conditions: Keep receptacle tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

— II



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredie	Ingredients with limit values that require monitoring at the workplace:		
1310-73-2	1310-73-2 sodium hydroxide		
OEL Shor	t-term	value: 2 mg/m³	
DNELs	DNELs		
15763-76-	15763-76-5 sodium p-cumenesulphonate		
Oral	DNEL	3.8 mg/kg×d (consumer)	
Dermal	DNEL	136.25 mg/kg×d (employee)	
		68.1 mg/kg×d (consumer)	
Inhalative	DNEL	26.9 mg/m3 (employee)	
		6.6 mg/m3 (consumer)	
1310-73-2	1310-73-2 sodium hydroxide		
Inhalative	DNEL	1 mg/m3 (employee)	
		1 mg/m3 (consumer)	
· PNECs			

15763-76-5 sodium p-cumenesulphonate

PNEC 0.23 mg/l (freshwater)
0.023 mg/l (marine water)
100 mg/l (STP)
PNEC sediment 0.862 mg/kg (freshwater)
0.086 mg/kg (marine water)
PNEC soil 0.037 mg/kg (soil)

8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A/P2.

· Hand protection



Protective gloves.

· Material of gloves Butyl rubber, BR

(Contd. on page 6)



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles (EN 166)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Physical state Liquid Yellow · Colour: · Odour: citrus-like

· Odour threshold: Not determined.

Melting point/freezing point: -7.5 °C

· Boiling point or initial boiling point and boiling range undetermined Not applicable.

Flammability

· Lower and upper explosion limit

Not determined. · Lower: · Upper: Not determined. · Flash point: Not applicable

Auto-ignition temperature: not applicable Decomposition temperature: Not determined.

pH at 20 °C 13.1 · pH-value 1 %: 11-12

· Viscosity:

· Kinematic viscosity Not determined.

· dynamic at 20 °C: 6 mPas

· Solubility

Fully miscible · Water: Not determined. · Partition coefficient n-octanol/water (log value) · Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C: 1.134 g/cm³ · Relative density Not determined. · Vapour density Not determined. Relative gas density Not determined. · Particle characteristics Not applicable.

9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

(Contd. on page 7)



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

	(Contd. of page	
· Explosive properties:	Product does not present an explosion hazard.	
Change in condition	,	
· Evaporation rate	Not determined.	
Information with regard to physical hazard class	ees	
Explosives	Void	
Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flammable gase	es es	
in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	May be corrosive to metals.	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity corresponds to 10.3
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Strong exothermic reaction with acids Reacts with light alloys to form hydrogen Corrodes aluminium

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Not compatible with alkali-sensitive substances like Sn, Zn, Al and paintings.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

		(Co	ontd. of page 7)
· LD/LC5	0 valu	ues relevant for classification:	
15763-7	'6-5 so	odium p-cumenesulphonate	
Oral	LD50) >5000 mg/kg (Rat) (OECD 401)	
Dermal	LD50	>2000 mg/kg (Rabbit)	
78330-2	0-8 fa	atty alcohol ethoxylate	
Oral	ATE	500 mg/kg (Rat)	
69011-3	6-5 is	sotridecanolethoxylate + 8 EO	
Oral	ATE	500 mg/kg (Rat)	
Oral	ATE	500 mg/kg (Rat)	

- Primary irritant effect:
- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- * STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity	· Aquatic toxicity:		
15763-76-5 sodiı	15763-76-5 sodium p-cumenesulphonate		
LC50/96 h (static)	>100 mg/l (Oncorhynchus mykiss)		
EC50/48 h (static)	>100 mg/l (Daphnia magna)		
EC50/96 h (static	>100 mg/l (Pseudokirchneriella subcapitata)		
1310-73-2 sodiur	n hydroxide		
LC50/96 h	125 mg/l (Gambusia affinis)		
EC50/48 h	76 mg/l (Daphnia magna)		
	40.4 mg/l (Ceriodaphnia dubia)		
EC50/15 min	22 mg/l (Photobacterium phosphoreum)		
78330-20-8 fatty	alcohol ethoxylate		
LC50/96 h	>10-100 mg/l (Leuciscus idus)		
EC50/48 h	>10-<100 mg/l (Aquatic invertebrates)		
EC50/72 h	>10-<100 mg/l (Aquatic plants)		
69011-36-5 isotri	69011-36-5 isotridecanolethoxylate + 8 EO		
LC50/96 h	>1-10 mg/l (Leuciscus idus)		
	(Contd. on page 9)		



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 8)

EC50/48 h	>1-10 mg/l (Aquatic invertebrates)
EC50/72 h	>1-10 mg/l (Aquatic plants)
NOEC	>1 mg/l /(21 d)

· 12.2 Persistence and degradability No further relevant information available.

Degree of elimination: 69011-36-5 isotridecanolethoxylate + 8 EO OECD 301B | >60 % (28 d) OECD 301E | ≥90 % (28 d)

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- Additional ecological information:
- · COD-value: 230000 mg/l
- · General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The product does not contain organically bounded halogens (AOX-free).

The contained organic complexing agents reach a DOC-elimination grade of 80% (corresponding to No. 406 of Annex "Analytic and measuring methods") and with this meet the tightened demands of Annex 49 of the revised Direction on liqid waste.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

(Contd. on page 10)



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 9)

· European waste catalogue

20 01 29* detergents containing hazardous substances

- · Uncleaned packaging:
- · Recommendation:
- Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
- · Recommended cleansing agents: Water, if necessary together with cleaning agents.

SECTION	11.	Transport	information
SECTION	14.	Transport	miormation

· 14.1 UN	number	or ID	number
-----------	--------	-------	--------

· ADR, IMDG, IATA UN1824

14.2 UN proper shipping name

ADR 1824 SODIUM HYDROXIDE SOLUTION

· IMDG, IATA SODIUM HYDROXIDE SOLUTION

14.3 Transport hazard class(es)

· ADR



· Class 8 (C5) Corrosive substances.

· Label 8

· IMDG, IATA



· Class 8 Corrosive substances.

· Label

14.4 Packing group

· ADR, IMDG, IATA

· **14.5 Environmental hazards:** Not applicable.

• 14.6 Special precautions for user Warning: Corrosive substances.

Hazard identification number (Kemler code): 80

EMS Number: F-A,S-B

· Segregation groups (SGG18) Alkalis

Stowage Category

· Segregation Code SG35 Stow "separated from" SGG1-acids

(Contd. on page 11)



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

	(Contd. of page 10)
14.7 Maritime transport in bulk according	
instruments	Not applicable.
Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
·IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1824 SODIUM HYDROXIDE SOLUTION, 8, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

A product information sheet can be provided if requested.

· Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

(Contd. on page 12)



Printing date 07.11.2025 Version number 10 (replaces version 9) Revision: 25.09.2024

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 11)

Classification according to Regulation (EC) No 1272/2008		
Corrosive to metals	On basis of test data	
Skin corrosion/irritation Serious eye damage/irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

Contact:

Regulatory Affairs Tel.: +49-7195-14-0

productsafety.management.de@karcher.com

· Version number of previous version: 9

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Met. Corr.1: Corrosive to metals – Category 1 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

* Data compared to the previous version altered.

· 0.011-350.0 RM806/14 2.773

· IE