

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** FloorPro High Gloss Crystallising Agent, powder RM 775
- **UFI:** N8J0-W0GV-U00H-SFM0
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
Restricted to professional users.
- **Application of the substance / the mixture**  
Discharging agent  
Surface active agent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
  
**Alfred Kärcher SE & Co. KG**  
Alfred-Kärcher-Str. 28-40  
D - 71364 Winnenden  
Tel.: +49-7195-14-0  
  
**Karcher Ltd**  
Unit 3  
Redcow Retail Centre  
Robinhood Road, Ballymount  
Dublin 22  
D22 PY03  
Tel.: +353 1 409 7777  
  
Internet: [www.karcher.com](http://www.karcher.com)
- **Further information obtainable from:**  
  
Regulatory Affairs  
Tel.: +49-7195-14-0  
[productsafety.management@de.kaercher.com](mailto:productsafety.management@de.kaercher.com)
- **1.4 Emergency telephone number:**  
Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre,  
Beaumont Hospital, Dublin 9 DOV2NO, Ireland.  
Telephone Number: +353 (0)1 809 2166  
  
For Hazardous Materials [or Dangerous Goods] Incidents  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night  
Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Acute Tox. 4 H302 Harmful if swallowed.

(Contd. on page 2)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 1)

Acute Tox. 4 H312 Harmful in contact with skin.

Eye Dam. 1 H318 Causes serious eye damage.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS05 GHS07

#### Signal word Danger

#### Hazard-determining components of labelling:

oxalic acid dihydrate

potassium trihydrogen dioxalate

#### Hazard statements

H302+H312 Harmful if swallowed or in contact with skin.

H318 Causes serious eye damage.

#### Precautionary statements

P280 Wear protective gloves / eye protection / face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P330 Rinse mouth.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Mixture of substances listed below with non-hazardous additions.

#### Dangerous components:

CAS: 127-96-8 EINECS: 204-874-6 Index number: 607-007-00-3 Reg.nr.: 01-0000012020-94-xxxx	potassium trihydrogen dioxalate ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312	≥30-≤50%
CAS: 6153-56-6 EINECS: 205-634-3 Index number: 607-006-00-8 Reg.nr.: 01-2119534576-33-xxxx	oxalic acid dihydrate ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312	≥20-≤30%

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 2)

CAS: 1344-28-1 EINECS: 215-691-6	aluminium oxide substance with a Community workplace exposure limit	≥10-≤20%
CAS: 7704-34-9 EINECS: 231-722-6 Index number: 016-094-00-1 Reg.nr.: 01-2119487295-27-XXXX	sulfur ⚠ Skin Irrit. 2, H315	≥1-<10%
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) substance with a Community workplace exposure limit	≥1-≤10%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**

Involve doctor immediately.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation** Supply fresh air; consult doctor in case of complaints.

· **After skin contact** Generally the product does not irritate the skin.

· **After eye contact** Rinse opened eye for several minutes under running water.

· **After swallowing**

Rinse out mouth and then drink plenty of water.

Call for a doctor immediately.

If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Causes severe skin burns and eye damage.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear fully protective suit.

· **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

IE  
(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 3)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
  - Do not allow product to reach sewage system or any water course.
  - Inform respective authorities in case of seepage into water course or sewage system.
  - Do not allow to enter sewers/ surface or ground water.
  - Do not allow to penetrate the ground/soil.
- **6.3 Methods and material for containment and cleaning up:**
  - Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
  - See Section 7 for information on safe handling
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
  - Use only in well ventilated areas.
  - Prevent formation of dust.
  - Avoid contact with eyes and skin.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
  - **Storage**
  - **Requirements to be met by storerooms and receptacles:** No special requirements.
  - **Information about storage in one common storage facility:** Keep away from food, beverages and feed.
  - **Further information about storage conditions:** Store in dry conditions.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

##### 1344-28-1 aluminium oxide

OEL	Long-term value: 10* 4** mg/m <sup>3</sup> *total inhalable **respirable dust
-----	--

##### 14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

OEL	Long-term value: 10* 0.8** mg/m <sup>3</sup> *total inhalable **respirable dust
-----	--

(Contd. on page 5)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 4)

- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Hand protection**



Protective gloves.

- **Material of gloves** Butyl rubber, BR
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact gloves made of the following materials are suitable:**  
\* butyl rubber 0,7 mm, 480 min (EN 374)
- **As protection from splashes gloves made of the following materials are suitable:**  
\* nitril rubber 0,4 mm, 30 min (EN 374)
- **Eye/face protection**



Tightly sealed goggles (EN 166)

- **Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Solid.
- **Colour:** Yellow
- **Odour:** Product specific
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** undetermined
- **Boiling point or initial boiling point and boiling range** undetermined
- **Flammability** Not determined.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** Not applicable
- **Ignition temperature:** not applicable

(Contd. on page 6)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 5)

· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not applicable.
· <b>dynamic:</b>	Not applicable.
· <b>Solubility</b>	
· <b>Water:</b>	Soluble
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure:</b>	Not applicable.
· <b>Density and/or relative density</b>	
· <b>Relative density</b>	Not determined.
· <b>Bulk density:</b>	915 kg/m <sup>3</sup>
· <b>Vapour density</b>	Not applicable.
· <b>Particle characteristics</b>	See item 3.

### · 9.2 Other information

· <b>Appearance:</b>	
· <b>Form:</b>	Solid.
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product does not present an explosion hazard.
· <b>Solvent content:</b>	
· <b>Solids content:</b>	100.0 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not applicable.

### · Information with regard to physical hazard classes

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void

(Contd. on page 7)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 6)

· Desensitised explosives

Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** corresponds to 10.3
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong alkali
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**  
Not suitable for surfaces that are attacked by acids (limestone, marble, brick, aluminium, etc.).  
metals
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed or in contact with skin.

· **LD/LC50 values relevant for classification:**
**127-96-8 potassium trihydrogen dioxalate**

Oral LD50 375 mg/kg (Rat)

**6153-56-6 oxalic acid dihydrate**

Dermal LD50 20,000 mg/kg (Rabbit)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 8)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 7)

### · 11.2 Information on other hazards

#### · Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

##### 127-96-8 potassium trihydrogen dioxalate

LC50/48 h | 160 mg/l (fish)

##### 6153-56-6 oxalic acid dihydrate

LC50/48 h | 160 mg/l (Leuciscus idus)

EC50/48 h | 162.2 mg/l (Daphnia magna)

### · 12.2 Persistence and degradability No further relevant information available.

### · 12.3 Bioaccumulative potential No further relevant information available.

### · 12.4 Mobility in soil No further relevant information available.

### · 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

### · 12.7 Other adverse effects

#### · Additional ecological information:

· **COD-value:** 250.000 mg/l

#### · General notes:

The product does not contain organically bounded halogens (AOX-free).

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## SECTION 13: Disposal considerations

### · 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

#### · European waste catalogue

20 01 29\* | detergents containing hazardous substances

(Contd. on page 9)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 8)

- **Uncleaned packaging:**
- **Recommendation:**  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.  
Non contaminated packagings may be recycled.  
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
- **Recommended cleansing agents:** Water, if necessary together with cleaning agents.

### SECTION 14: Transport information

- |   |                 |
|---|-----------------|
| · <b>14.1 UN number or ID number</b><br>· <b>ADR, ADN, IMDG, IATA</b>                       | Void            |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR, ADN, IMDG, IATA</b>                      | Void            |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR, ADN, IMDG, IATA</b><br>· <b>Class</b> | Void            |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>                                     | Void            |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>                          | No              |
| · <b>14.6 Special precautions for user</b>  | Not applicable. |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b>                       | Not applicable. |
| · <b>UN "Model Regulation":</b>   | Void            |

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.01.2023

Version number 8 (replaces version 7)

Revision: 21.11.2022

**Trade name: FloorPro High Gloss Crystallising Agent, powder RM 775**

(Contd. of page 9)

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.  
A product information sheet can be provided if requested.

#### • Relevant phrases

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.

#### • Classification according to Regulation (EC) No 1272/2008

Acute toxicity - oral Acute toxicity - dermal Serious eye damage/eye irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
---	--

#### • Contact:

Regulatory Affairs  
Tel.: +49-7195-14-0  
productsafety.management@de.kaercher.com

#### • Version number of previous version: 7

#### • Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

#### • \* Data compared to the previous version altered.

• 0-011-676-0 RM 775/3 2-449