

**Safety data sheet
according to UK REACH**

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** VehiclePro Hot Wax RM 820 Classic**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Restricted to professional users.

Application of the substance / the mixture Drying aid for vehicle washing plants**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:****Alfred Kärcher SE & Co. KG**

Alfred-Kärcher-Str. 28-40

D - 71364 Winnenden

Tel.: +49-7195-14-0

Kärcher (UK) Ltd.

Kärcher House

Brookhill Way

Banbury

Oxon OX16 3ED

Great Britain

Tel.: +44-1295-752-000

Internet: www.karcher.com**Further information obtainable from:**

Regulatory Affairs

Tel.: +49-7195-14-0

productsafety.management.de@karcher.com**1.4 Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 1)

Hazard pictograms



GHS05

Signal word Danger

Hazard-determining components of labelling:

Aminosiloxane

1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates

Hazard statements

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

CAS: 5131-66-8 EINECS: 225-878-4 Index number: 603-052-00-8 Reg.nr.: 01-2119475527-28-XXXX	propylene glycol monobutyl ether ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥5-<10%
CAS: 71750-79-3	Aminosiloxane ⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315	≥2.5-<3%
CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2, H319	1-5%
CAS: 1474044-71-7 EC number: 939-685-4 Reg.nr.: 01-2119983493-26	1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; ⚠ Aquatic Chronic 3, H412	≥1-<2.5%
CAS: 9004-78-8	Phenol, ethoxylated ⚠ Acute Tox. 4, H302	0.1-1%

Additional information For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

**Safety data sheet
according to UK REACH**

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 2)

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact** Generally the product does not irritate the skin.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.**· 4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.**SECTION 5: Firefighting measures****· 5.1 Extinguishing media****· Suitable extinguishing agents**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**· 5.2 Special hazards arising from the substance or mixture** No further relevant information available.**· 5.3 Advice for firefighters**

- **Protective equipment:** No special measures required.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures** Not required**· 6.2 Environmental precautions:**

- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

· 6.4 Reference to other sections

- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: **VehiclePro Hot Wax RM 820 Classic**

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Avoid contact with eyes and skin.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Keep away from food, beverages and feed.
- **Further information about storage conditions:** Protect from frost.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

112-34-5 2-(2-butoxyethoxy)ethanol

WEL	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
-----	--

· **PNECs**

1474044-71-7 1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates

PNEC	10 mg/l (STP) (Assessment factor: 100)
PNEC sediment	1.7 mg/kg (freshwater) (sediment dw) 0.17 mg/kg (marine water) (sediment dw)
PNEC aqua	0.017 mg/l (freshwater) (Assessment factor: 10) 0.002 mg/l (marine water) (Assessment factor: 100)

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Hand protection** Not required
- **Material of gloves** Not required
- **Penetration time of glove material** Not required

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 4)

· Eye/face protection



Tightly sealed goggles (EN 166)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Liquid
· Colour:	Red
· Odour:	Pine
· Odour threshold:	Not determined
· Melting point/freezing point:	-1 °C
· Boiling point or initial boiling point and boiling range	undetermined
· Flammability	Not applicable
· Lower and upper explosion limit	
· Lower:	Not determined
· Upper:	Not determined
· Flash point:	Not applicable
· Auto-ignition temperature:	not applicable
· Decomposition temperature:	Not determined
· pH at 20 °C	3.9
· pH-value 1 %:	6-8
· Viscosity:	
· Kinematic viscosity	Not determined
· dynamic:	Not determined
· Solubility	
· Water:	Fully miscible
· Partition coefficient n-octanol/water (log value)	Not determined
· Vapour pressure:	Not determined
· Density and/or relative density	
· Density at 20 °C:	0.999 g/cm ³
· Relative density	Not determined
· Vapour density	Not determined
· Relative gas density	Not determined

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 5)

- Change in condition
- Evaporation rate Not determined

Information with regard to physical hazard classes

- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Void
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** corresponds to 10.3
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

5131-66-8 propylene glycol monobutyl ether

Oral	LD50	3300 mg/kg (Rat)
------	------	------------------

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 6)

112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	2410 mg/kg (mouse) (OECD 401)
Dermal	LD50	2764 mg/kg (Rabbit)

9004-78-8 Phenol, ethoxylated

Oral	LD50	500-2000 mg/kg (Rat)
Dermal	LD50	2140 mg/kg (Rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

5131-66-8 propylene glycol monobutyl ether

LC50/96 h 560-1000 mg/l (fish)

112-34-5 2-(2-butoxyethoxy)ethanol

LC50/96 h	1300 mg/l (Lepomis macrochirus)
EC10/16 h	1170 mg/l (Pseudomonas putida)
EC50/24 h	2850 mg/l (Daphnia magna) (DIN 38412)
NOEC	>100 mg/l (Desmodesmus subspicatus)

1474044-71-7 1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates

LC50/96 h	>10 mg/l (Cyprinus carpio)
EC50/48 h	>8.6 mg/l (Daphnia magna)
EC50/72 h (static)	1.2 mg/l (Pseudokirchneriella subcapitata)
EC50	100 mg/l /6 d (STP)
NOEC	0.686 mg/l /35 d (Pimephales promelas)
	1 mg/l /21 d (Daphnia magna)
	0.39 mg/l /72 h (Pseudokirchneriella subcapitata) (OECD 201)

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: **VehiclePro Hot Wax RM 820 Classic**

(Contd. of page 7)

· **12.2 Persistence and degradability** No further relevant information available.

· **Degree of elimination:**

5131-66-8 propylene glycol monobutyl ether

OECD 301E 90 % (28 d)

112-34-5 2-(2-butoxyethoxy)ethanol

OECD 301C 80-90 % (28 d)

OECD 301E >70 % (28 d)

OECD 302B 100 % (28 d)

1474044-71-7 1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates

OECD 301F >60 % (28 d)

OECD 311 >60 % (60 d)

9004-78-8 Phenol, ethoxylated

OECD 301F 79 % (28 d)

OECD 311 >60 % (60 d)

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable

· **vPvB:** Not applicable

· **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **COD-value:** 338000 mg/l

· **General notes:**

The product does not contain organic complexing agents.

The product does not contain organically bounded halogens (AOX-free).

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 8)

· European waste catalogue

20 01 29* | detergents containing hazardous substances

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Water, if necessary together with cleaning agents.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

Not applicable

· 14.6 Special precautions for user

Not applicable

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable

· UN "Model Regulation":

Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

(Contd. on page 10)

**Safety data sheet
according to UK REACH**

Printing date 15.05.2026

Version number 10 (replaces version 9)

Revision: 12.01.2026

Trade name: VehiclePro Hot Wax RM 820 Classic*(Contd. of page 9)*

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
A product information sheet can be provided if requested.

- **Relevant phrases**
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- **Contact:**
Regulatory Affairs
Tel.: +49-7195-14-0
productsafety.management.de@karcher.com
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
- *** Data compared to the previous version altered.**
- 0-011-775-0 RM 820 Classic/3 2-906