

Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: VehiclePro Spray Wax RM 821 Classic
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Restricted to professional users.
- · Application of the substance / the mixture Drying aid for vehicle washing plants
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

### Alfred Kärcher SE & Co. KG

Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden Tel.: +49-7195-14-0

#### Karcher Ltd

Unit 3
Redcow Retail Centre
Robinhood Road, Ballymount
Dublin 22
D22 PY03

Tel.: +353 1 409 7777

Internet: www.karcher.com

## · Further information obtainable from:

Regulatory Affairs Tel.: +49-7195-14-0

productsafety.management.de@karcher.com

### 1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont

Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

For Hazardous Materials [or Dangerous Goods] Incidents

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

## **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 1)

- · Hazard pictograms Void
- · Signal word Void
- Hazard statements

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

### 2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

Results of PBT and vPvB assessment

=	=	_	_
Р	R	т	•

541-02-6 decamethylcyclopentasiloxane

#### · vPvB:

541-02-6 decamethylcyclopentasiloxane

## Determination of endocrine-disrupting properties

Not applicable.

541-02-6 decamethylcyclopentasiloxane

List II

## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

• **Description:** Mixture of substances listed below with non-hazardous additions.

Dangerous components:		
CAS: 1335202-95-3 EC number: 931-216-1 Reg.nr.: 01-2119472309-33	Fatty acids, C18 unsatd., reaction productswith triethanolamine, di-Me sulfate-quaternized  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412  Specific concentration limits: Skin Irrit. 2; H315: C ≥ 28 %  Eye Irrit. 2; H319: C ≥ 28 %	1-5%
CAS: 541-02-6 EINECS: 208-764-9 Reg.nr.: 01-2119511367-43-0000	decamethylcyclopentasiloxane Non-classified vPvB substance. Non-classified PBT substance. Substance identified as having endocrine disrupting properties (II).	≥1-≤5%
CAS: 5131-66-8 EINECS: 225-878-4 Index number: 603-052-00-8 Reg.nr.: 01-2119475527-28-XXXX	propylene glycol monobutyl ether  Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Flam. Liq. 2, H225;	1-5%
CAS: 5989-27-5 EINECS: 227-813-5 Index number: 601-096-00-2 Reg.nr.: 01-2119529223-47	(R)-p-mentha-1,8-diene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Skin Irrit. 2, H315; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	≥0.25-<1%

(Contd. on page 3)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

			(Contd. of page 2)
	CAS: 68424-85-1 EINECS: 270-325-2	Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))	≥0.1-<0.25%
	Reg.nr.: 01-2119965180-41	Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302	
Ī	·SVHC		
ı	541-02-6 decamethylcyclopentasi	oxane	
Ī	Regulation (EC) No 648/2004	on detergents / Labelling for contents	
ı	cationic surfactants		<5%
Ī	perfumes (LIMONENE, alpha-Hex	ylcinnamaldehyde)	
_	Additional information For the	wording of the listed hazard phrases refer to section 16.	

### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Rinse with warm water.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

### **SECTION 6: Accidental release measures**

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 4)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

## 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

## · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage

Inhalative

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Keep away from food, beverages and feed.
- Further information about storage conditions: Protect from frost.
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

DNEL 500 mg/m3 (employee) 89 mg/m3 (consumer)

### 8.1 Control parameters

· Ingre	Ingredients with limit values that require monitoring at the workplace:		
67-63	-0 propan-	-2-ol	
	OEL Short-term value: 400 ppm Long-term value: 200 ppm Sk		
· DNEL	-S		
67-63	67-63-0 propan-2-ol		
Oral		DNEL	26 mg/kg×d (consumer)
Derm	al	DNEL	888 mg/kg×d (employee)
			319 mg/kg×d (consumer)

(Contd. on page 5)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

	(Contd. of page 4
_	I (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))
Dermal	DNEL 5.7 mg/kg×d (employee)
Inhalative	DNEL 3.96 mg/m3 (employee)
	1.64 mg/m3 (consumer)
Irritation of skin	DNEL 3.4 mg/cm2 (consumer)
PNECs	
	ethylcyclopentasiloxane
PNEC	10 mg/l (STP) (Assessment factor: 100)
PNEC sediment	11 mg/kg (freshwater) (Assessment factor: 10)
	1.1 mg/kg (marine water) (Assessment factor: 100)
PNEC soil	2.54 mg/kg (Assessment factor: 50)
PNEC aqua	0.0012 mg/l (freshwater) (Assessment factor: 10)
	0.00012 mg/l (marine water) (Assessment factor: 100)
67-63-0 propan-	
PNEC	140.9 mg/l (freshwater)
	140.9 mg/l (marine water)
	140.9 mg/l (STP)
	2251 mg/l (STP)
PNEC sediment	552 mg/kg (freshwater)
	552 mg/kg (marine water)
PNEC soil	28 mg/kg (soil)
	mentha-1,8-diene
PNEC	1.8 mg/l (STP) (Assessment factor: 10)
PNEC sediment	3.85 mg/kg (freshwater) (sediment dw)
	0.385 mg/kg (marine water) (sediment dw)
PNEC soil	0.763 mg/kg (soil dw)
PNEC aqua	0.014 mg/l (freshwater) (Assessment factor: 10)
	0.0014 mg/l (marine water) (Assessment factor: 100)
	l (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))
PNEC	0.001 mg/l (freshwater)
	0.001 mg/l (marine water)
	0.4 mg/l (STP)
PNEC sediment	12.27 mg/kg (freshwater)
	13.09 mg/kg (marine water)
PNEC soil	7 mg/kg (soil)

- 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

(Contd. on page 6)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 5)

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection
- \* chemical resistant protective gloves (EN 374)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Not applicable.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Not required.
- Penetration time of glove material Not required.
- For the permanent contact gloves made of the following materials are suitable:
- \* butyl rubber 0,7 mm, 480 min (EN 374)
- · As protection from splashes gloves made of the following materials are suitable:
- \* nitril rubber 0,4 mm, 30 min (EN 374)
- · Eye/face protection Goggles recommended during refilling.

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

General Information

Physical stateColour:Odour:fresh

· Odour threshold: Not determined.

Melting point/freezing point: 0 °C

· Boiling point or initial boiling point and boiling range 100 °C

· Flammability

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: Not applicable
 Auto-ignition temperature: not applicable
 Decomposition temperature: Not determined.

PH at 20 °C 4

• pH-value 1 %: 6-8

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.3 mPas

· Solubility

Water: Fully miscible
 Partition coefficient n-octanol/water (log value) Not determined.
 Vapour pressure: Not determined.

Density and/or relative density

Density and/or relative density

Density at 20 °C:

Relative density

Vapour density

Not determined.

Relative gas density

Not determined.

Particle characteristics

Not applicable.

(Contd. on page 7)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 6)

		info	

Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Solids content: 5.1 %

· Change in condition

• Evaporation rate Not determined.

## Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases	
in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity corresponds to 10.3
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 7)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

## **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:		
541-02-6	541-02-6 decamethylcyclopentasiloxane		
Dermal	LD50	>15000 mg/kg (Rat)	
Inhalative	LC50	>5000 mg/kg (Rat)	
5131-66-8	propy	rlene glycol monobutyl ether	
Oral	ral LD50 3300 mg/kg (Rat)		
67-63-0 pi	ropan-	2-ol	
Oral	LD50	5840 mg/kg (Rat) (OECD 401)	
Dermal	Dermal LD50 13900 mg/kg (Rabbit) (OECD 402)		
68424-85-	68424-85-1 Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))		
Oral	LD50	344 mg/kg (Rat)	
Dermal	LD50	3340 mg/kg (Rabbit)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

· Endocri	· Endocrine disrupting properties		
541-02-6	decamethylcyclopentasiloxane	List II	
540-97-6	Dodecamethylcyclohexasiloxane	List II	
118-58-1	benzyl salicylate	List II	
556-67-2	octamethylcyclotetrasiloxane	List II; III	

(Contd. on page 9)

— IE



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 8)

# **SECTION 12: Ecological information**

## · 12.1 Toxicity

	·-·· · · · · · · · · · · · · · · · · ·		
Aquatic tox	· Aquatic toxicity:		
5131-66-8 pr	5131-66-8 propylene glycol monobutyl ether		
LC50/96 h	560-1000 mg/l (fish)		
67-63-0 prop	an-2-ol		
LC50/96 h	9640 mg/l (Pimephales promelas)		
EC50/48 h	13299 mg/l (Daphnia magna)		
EC50/72 h	>1000 mg/l (Desmodesmus subspicatus)		
EC10/18 h	>1000 mg/l (Pseudomonas putida) (DIN 38412)		
5989-27-5 (R	)-p-mentha-1,8-diene		
LC50/96 h	0.72 mg/l (Pimephales promelas)		
EC50/48 h	0.307 mg/l (Daphnia magna)		
	0.25 mg/l (Pseudokirchneriella subcapitata)		
EC50/72 h	0.32 mg/l (Pseudokirchneriella subcapitata)		
EC10/72 h	0.174 mg/l (Pseudokirchneriella subcapitata)		
EC10/21 d	EC10/21 d 0.153 mg/l (Daphnia magna)		
EC10/8 d	0.37-0.67 mg/l (Pimephales promelas)		
EC50/3h	209 mg/l (activated sludge) (OECD 209)		
68424-85-1 A	lkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))		
LC50/96 h	0.28 mg/l (Pimephales promelas) (US-EPA)		
	0.515 mg/l (Lepomis macrochirus)		
IC50/72 h	0.03 mg/l (Algae)		
EC50/48 h	0.016 mg/l (Daphnia magna)		
EC50/30 min	11 mg/l (activated sludge) (OECD 209)		
ErC50/96h	0.049 mg/l (Pseudokirchneriella subcapitata)		
NOEC	0.032 mg/l (Pimephales promelas)		
	0.0042 mg/l (Daphnia magna)		
	0.456 mg/l (Lepomis macrochirus)		

## · 12.2 Persistence and degradability No further relevant information available.

Degree of elimination:	
1335202-95-3 Fatty acids, C18 unsatd., reaction products with triethanolamine, di-Me sulfate-quaternized	
OECD 301B  >60 % (28 d)	
541-02-6 decamethylcyclopentasiloxane	
OECD 310 0.14 % (28 d)	
5131-66-8 propylene glycol monobutyl ether	
OECD 301E 90 % (28 d)	
5989-27-5 (R)-p-mentha-1,8-diene	
OECD 301B   71.4 % (28 d)	10)

(Contd. on page 10)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 9)

### 68424-85-1 Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))

OECD 301D 63 % (28 d)

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT:

541-02-6 decamethylcyclopentasiloxane

· vPvB:

541-02-6 decamethylcyclopentasiloxane

- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- · COD-value: 219000 mg/l
- · General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The product does not contain organic complexing agents.

The product does not contain organically bounded halogens (AOX-free).

Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue

20 01 29\* detergents containing hazardous substances

- Uncleaned packaging:
- · Recommendation:

Packaging may be reused or recycled after cleaning.

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 11)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

· Recommended cleansing agents: Water, if necessary together with cleaning agents.

(Contd. of page 10)

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.
UN "Model Regulation":	Void

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 70
- National regulations
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57
  541-02-6 | decamethylcyclopentasiloxane
  - · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

- 10



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 11)

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

A product information sheet can be provided if requested.

### Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

## Classification according to Regulation (EC) No 1272/2008

Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### · Contact:

Regulatory Affairs Tel.: +49-7195-14-0

productsafety.management.de@karcher.com

### · Version number of previous version: 6

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

(Contd. on page 13)



Printing date 18.05.2024 Version number 7 (replaces version 6) Revision: 21.11.2022

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 12)

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

\* Data compared to the previous version altered.

0.011-776.0

RM 821/11

2.051

.\_