

Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: VehiclePro Super Pearl Wax RM 824 Classic
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Restricted to professional users.



Keep away from children.

- Application of the substance / the mixture Drying aid for vehicle washing plants
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Alfred Kärcher SE & Co. KG

Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden Tel.: +49-7195-14-0

Karcher Ltd

Unit 3 Redcow Retail Centre Robinhood Road, Ballymount Dublin 22 D22 PY03

Tel.: +353 1 409 7777

Internet: www.karcher.com

Further information obtainable from:

Regulatory Affairs
Tel.: +49-7195-14-0

products a fety. management. de@karcher.com

· 1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont

Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

For Hazardous Materials [or Dangerous Goods] Incidents

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Additional information:

Safety data sheet available on request.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- · PBT:

Not applicable.

541-02-6	decamethylcyclopentasiloxane
540-97-6	Dodecamethylcyclohexasiloxane

· vPvB:

Not applicable.

541-02-6	decamethylcyclopentasiloxane
540-97-6	Dodecamethylcyclohexasiloxane

Determination of endocrine-disrupting properties

Not applicable.

541-02-6 decamethylcyclopentasiloxane	List II
540-97-6 Dodecamethylcyclohexasiloxane	List II

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- **Description:** Mixture of substances listed below with non-hazardous additions.

Dangerous	components:
-----------	-------------

CAS: 1335202-95-3	Fatty acids, C18 unsatd., reaction productswith triethanolamine, di-Me	≥2.5-<5%
EC number: 931-216-1	sulfate-quaternized	
Reg.nr.: 01-2119472309-33	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	
	Specific concentration limits: Skin Irrit. 2; H315: C ≥ 28 %	
	Eye Irrit. 2; H319: C ≥ 28 %	

(Contd. on page 3)



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

CAS: 541-02-6	decamethylcyclopentasiloxane	(Contd. of page ≥1-≤5%
EINECS: 208-764-9	Non-classified vPvB substance.	
Reg.nr.: 01-2119511367-43-0000	Non-classified PBT substance.	
	Substance identified as having endocrine disrupting properties (II).	
CAS: 5131-66-8	propylene glycol monobutyl ether	1-5%
EINECS: 225-878-4	(1) Skin Irrit. 2, H315; Eye Irrit. 2, H319	1
Index number: 603-052-00-8		
Reg.nr.: 01-2119475527-28-XXXX		
CAS: 67-63-0	propan-2-ol	1-5%
EINECS: 200-661-7	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	1
Index number: 603-117-00-0		
Reg.nr.: 01-2119457558-25-xxxx		
CAS: 112-34-5	2-(2-butoxyethoxy)ethanol	1-5%
EINECS: 203-961-6	♦ Eye Irrit. 2, H319	1
Index number: 603-096-00-8		
Reg.nr.: 01-2119475104-44-xxxx		
CAS: 540-97-6	Dodecamethylcyclohexasiloxane	≥0-≤1%
EINECS: 208-762-8	Non-classified vPvB substance.	
Reg.nr.: 01-2119517435-42	Non-classified PBT substance.	
	Substance identified as having endocrine disrupting properties (II).	
SVHC		
541-02-6 decamethylcyclopentasil	oxane	
540-97-6 Dodecamethylcyclohexas	siloxane	

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Generally the product does not irritate the skin.
- · After eye contact Rinse opened eye for several minutes under running water.
- After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 3)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

- 6.4 Reference to other sections
- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Keep away from food, beverages and feed.
- · Further information about storage conditions: Protect from frost.
- · 7.3 Specific end use(s) No further relevant information available.



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

67-63-0 propan	ith limit values that require monitoring at the workplace: -2-ol
OEL Short-term	value: 400 ppm
Long-term Skin	value: 200 ppm
112-34-5 2-(2-b	utoxyethoxy)ethanol
	value: 101.2 mg/m³, 12 ppm
Long-term IOELV	value: 67.5 mg/m³, 10 ppm
DNELs	
67-63-0 propan	-2-ol
Oral	DNEL 26 mg/kg×d (consumer)
Dermal	DNEL 888 mg/kg×d (employee)
	319 mg/kg×d (consumer)
Inhalative	DNEL 500 mg/m3 (employee)
	89 mg/m3 (consumer)
68424-85-1 Alk	yl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))
Dermal	DNEL 5.7 mg/kg×d (employee)
Inhalative	DNEL 3.96 mg/m3 (employee)
	1.64 mg/m3 (consumer)
Irritation of skin	DNEL 3.4 mg/cm2 (consumer)
PNECs	
	nethylcyclopentasiloxane
PNEC 10 mg/l (STP) (Assessment factor: 100)	
PNEC sediment	11 mg/kg (freshwater) (Assessment factor: 10)
	1.1 mg/kg (marine water) (Assessment factor: 100)
PNEC soil	2.54 mg/kg (Assessment factor: 50)
PNEC aqua	0.0012 mg/l (freshwater) (Assessment factor: 10)
	0.00012 mg/l (marine water) (Assessment factor: 100)
67-63-0 propan	-2-ol
PNEC	140.9 mg/l (freshwater)
	140.9 mg/l (marine water)
	140.9 mg/l (STP)
	2251 mg/l (STP)
PNEC sediment	552 mg/kg (freshwater)
	552 mg/kg (marine water)
PNEC soil	28 mg/kg (soil)



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 5)

		(Conta. or page 5)
68424-85-1 Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))		
PNEC	0.001 mg/l (freshwater)	
	0.001 mg/l (marine water)	
	0.4 mg/l (STP)	
PNEC sediment	12.27 mg/kg (freshwater)	
	13.09 mg/kg (marine water)	

8.2 Exposure controls

PNEC soil

- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures Wash hands before breaks and at the end of work.
- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection Not required.
- Material of gloves Not required.
- · Penetration time of glove material Not required.

7 mg/kg (soil)

· Eye/face protection Not required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateColour:Odour:Pine

· Odour threshold: Not determined.

· Melting point/freezing point: 0 °C

Boiling point or initial boiling point and boiling range
 Flammability
 undetermined
 Not applicable.

· Lower and upper explosion limit

Lower:

Vipper:

Flash point:

Auto-ignition temperature:

Decomposition temperature:

Not determined.

Not applicable

not applicable

Not determined.

Decomposition temperature:

PH at 20 °C

PH-value 1 %:

Not

4

6-8

Viscosity:

· Kinematic viscosity Not determined.

· dynamic at 20 °C: 5 mPas

· Solubility

Water: Fully miscible
 Partition coefficient n-octanol/water (log value) Not determined.
 Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 0.992 g/cm³

(Contd. on page 7)



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

	(Contd. of page 6)
· Relative density	Not determined.
· Vapour density	Not determined.
Relative gas density	Not determined.
· Particle characteristics	Not applicable.
9.2 Other information	
· Appearance:	
Form:	Fluid
Important information on protection of health and	riuiu
•	
environment, and on safety.	Due doublie was a self-weighten
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
· Evaporation rate	Not determined.
Information with regard to physical hazard classes	S
Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases	
in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity corresponds to 10.3
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 7)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
541-02-6 c	541-02-6 decamethylcyclopentasiloxane		
Dermal	LD50	>15000 mg/kg (Rat)	
Inhalative	LC50	>5000 mg/kg (Rat)	
		lene glycol monobutyl ether	
Oral	LD50	3300 mg/kg (Rat)	
67-63-0 pr	67-63-0 propan-2-ol		
Oral	LD50	5840 mg/kg (Rat) (OECD 401)	
Dermal	LD50	13900 mg/kg (Rabbit) (OECD 402)	
112-34-5 2	112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	2410 mg/kg (mouse) (OECD 401)	
Dermal	LD50	2764 mg/kg (Rabbit)	
68424-85-	68424-85-1 Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))		
Oral	LD50	344 mg/kg (Rat)	
Dermal	LD50	3340 mg/kg (Rabbit)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

Endocrine disrupting properties		
541-02-6 decamethylcyclopentasiloxane	List II	
540-97-6 Dodecamethylcyclohexasiloxane	List II	
556-67-2 octamethylcyclotetrasiloxane	List II	

(Contd. on page 9)

_ 1



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 8)

SECTION 12: Ecological information

· 12.1 Toxicity

	12.1 Toxiony		
· Aquatic tox	· Aquatic toxicity:		
5131-66-8 propylene glycol monobutyl ether			
LC50/96 h	560-1000 mg/l (fish)		
67-63-0 prop	67-63-0 propan-2-ol		
LC50/96 h	9640 mg/l (Pimephales promelas)		
EC50/48 h	13299 mg/l (Daphnia magna)		
EC50/72 h	>1000 mg/l (Desmodesmus subspicatus)		
EC10/18 h	>1000 mg/l (Pseudomonas putida) (DIN 38412)		
112-34-5 2-(2	-butoxyethoxy)ethanol		
LC50/96 h	1300 mg/l (Lepomis macrochirus)		
EC10/16 h	1170 mg/l (Pseudomonas putida)		
EC50/24 h	2850 mg/l (Daphnia magna) (DIN 38412)		
NOEC	>100 mg/l (Desmodesmus subspicatus)		
68424-85-1 A	lkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))		
LC50/96 h	0.28 mg/l (Pimephales promelas) (US-EPA)		
	0.515 mg/l (Lepomis macrochirus)		
IC50/72 h	0.03 mg/l (Algae)		
EC50/48 h	0.016 mg/l (Daphnia magna)		
EC50/30 min	11 mg/l (activated sludge) (OECD 209)		
ErC50/96h	0.049 mg/l (Pseudokirchneriella subcapitata)		
NOEC	0.032 mg/l (Pimephales promelas)		
	0.0042 mg/l (Daphnia magna)		
	0.456 mg/l (Lepomis macrochirus)		

· 12.2 Persistence and degradability No further relevant information available.

Degree of	elimination:
1335202-95-	3 Fatty acids, C18 unsatd., reaction productswith triethanolamine, di-Me sulfate-quaternized
OECD 301B	>60 % (28 d)
541-02-6 ded	amethylcyclopentasiloxane
OECD 310	0.14 % (28 d)
5131-66-8 pr	opylene glycol monobutyl ether
OECD 301E	90 % (28 d)
•	2-butoxyethoxy)ethanol
OECD 301C	80-90 % (28 d)
OECD 301E	>70 % (28 d)
OECD 302B	100 % (28 d)
	(Contd. on page 1

10,



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 9)

68424-85-1 Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))

OECD 301D 63 % (28 d)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

· PBT:		
	decamethylcyclopentasiloxane	
540-97-6	Dodecamethylcyclohexasiloxane	
· vPvB:		
541-02-6	decamethylcyclopentasiloxane	
540-97-6	Dodecamethylcyclohexasiloxane	

- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- Additional ecological information:
- · COD-value: 325.000 mg/l
- · General notes:

The product does not contain organic complexing agents.

The product does not contain organically bounded halogens (AOX-free).

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue

20 01 30 detergents other than those mentioned in 20 01 29

- Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Water, if necessary together with cleaning agents.

(Contd. on page 11)



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 10)

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according instruments	to IMO Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 70
- National regulations
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57	
541-02-6	decamethylcyclopentasiloxane
540-97-6	Dodecamethylcyclohexasiloxane

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

A product information sheet can be provided if requested.

(Contd. on page 12)



Printing date 13.06.2025 Version number 8 (replaces version 7) Revision: 10.06.2025

Trade name: VehiclePro Super Pearl Wax RM 824 Classic

(Contd. of page 11)

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Contact:

Regulatory Affairs Tel.: +49-7195-14-0

Tel.: +49-7195-14-0

productsafety.management.de@karcher.com

· Version number of previous version: 7

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

· 0.011-779.0 RM 824 Classic/2 2.836

IE -