

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: FloorPro Crystallising Agent RM 749**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Restricted to professional users.
- **Application of the substance / the mixture** Surface active agent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

Alfred Kärcher SE & Co. KG
Alfred-Kärcher-Str. 28-40
D - 71364 Winnenden
Tel.: +49-7195-14-0

Kärcher (UK) Ltd.
Kärcher House
Brookhill Way
Banbury
Oxon OX16 3ED
Great Britain
Tel.: +44-1295-752-000

Internet: www.karcher.com
- **Further information obtainable from:**

Regulatory Affairs
Tel.: +49-7195-14-0
productsafety.management@de.kaercher.com
- **1.4 Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Met. Corr.1 H290 May be corrosive to metals.
Skin Corr. 1 H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 1)

· Hazard pictograms



GHS05

· Signal word Danger

· Hazard-determining components of labelling:

magnesium hexafluorosilicate hexahydrate

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:

CAS: 18972-56-0 EINECS: 241-022-2 Index number: 009-018-00-3 Reg.nr.: 01-2119980031-47-0000	magnesium hexafluorosilicate hexahydrate ⚠ Acute Tox. 3, H301; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H332; Aquatic Chronic 3, H412	5-10%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1-5%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35-XXXX	1-methoxypropan-2-ol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	1-5%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 2)

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information**

Involve doctor immediately.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation**

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- **After skin contact** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **5.2 Special hazards arising from the substance or mixture** Siliciumtetrafluoride

- **5.3 Advice for firefighters**

- **Protective equipment:** Wear self-contained respiratory protective device.

- **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 3)

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Avoid contact with eyes and skin.

· **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
· **Information about storage in one common storage facility:** Keep away from food, beverages and feed.
· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

107-98-2 1-methoxypropan-2-ol

WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
Sk	

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 4)

· DNELs

67-63-0 propan-2-ol

Oral	DNEL	26 mg/kg*d (consumer)
Dermal	DNEL	888 mg/kg*d (employee) 319 mg/kg*d (consumer)
Inhalative	DNEL	500 mg/m3 (employee) 89 mg/m3 (consumer)

· PNECs

67-63-0 propan-2-ol

PNEC	140.9 mg/l (freshwater) 140.9 mg/l (marine water) 140.9 mg/l (STP) 2251 mg/l (STP)
PNEC sediment	552 mg/kg (freshwater) 552 mg/kg (marine water)
PNEC soil	28 mg/kg (soil)

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Do not inhale gases / fumes / aerosols.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2.

· **Hand protection**

Acid resistant gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves.

· **Material of gloves** Butyl rubber, BR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 5)

· Eye/face protection



Tightly sealed goggles (EN 166)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Fluid
· Colour:	Cloudy
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	-6.5 °C
· Boiling point or initial boiling point and boiling range	100 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	45 °C
· Ignition temperature:	Does not support burning
· Decomposition temperature:	not applicable
· pH at 20 °C	Not determined.
· Viscosity:	0.8
· Kinematic viscosity	
· dynamic at 20 °C:	Not determined.
· Solubility	3 mPas
· Water:	Fully miscible
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.039 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Relative gas density	Not determined.
· Particle characteristics	Not applicable.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 6)

· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	May be corrosive to metals.
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** corresponds to 10.3
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with strong alkali
Reacts with light alloys to form hydrogen
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 7)

· LD/LC50 values relevant for classification:

18972-56-0 magnesium hexafluorosilicate hexahydrate

Oral	LD50	291 mg/kg (Rat)
Inhalative	LC50/4 h	3.6 mg/l (Rat)
	LC50/1h	14.4 mg/l (Rat)

67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (Rat) (OECD 401)
Dermal	LD50	13900 mg/kg (Rabbit) (OECD 402)

107-98-2 1-methoxypropan-2-ol

Oral	LD50	4016 mg/kg (Rat)
------	------	------------------

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

18972-56-0 magnesium hexafluorosilicate hexahydrate

LC50/96 h	10-100 mg/l (fish)
EC50	10-100 mg/l (Algae)

67-63-0 propan-2-ol

LC50/96 h	9640 mg/l (Pimephales promelas)
EC50/48 h	13299 mg/l (Daphnia magna)
EC50/72 h	>1000 mg/l (Desmodesmus subspicatus)
EC10/18 h	>1000 mg/l (Pseudomonas putida) (DIN 38412)

107-98-2 1-methoxypropan-2-ol

LC50/96 h	6812 mg/l (Leuciscus idus) (DIN 38412)
-----------	--

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is biodegradable.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 8)

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **COD-value:** 220.000 mg/l

· **General notes:**

The product does not contain organically bounded halogens (AOX-free).

The product does not contain organic complexing agents.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

· **European waste catalogue**

06 03 14	solid salts and solutions other than those mentioned in 06 03 11 and 06 03 13
----------	---

· **Uncleaned packaging:**

· **Recommendation:**

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· **Recommended cleansing agents:** Water, if necessary together with cleaning agents.

GB

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 9)

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN3264
· 14.2 UN proper shipping name	
· ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (MAGNESIUM FLUOROSILICATE, HYDROCHLORIC ACID)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (MAGNESIUM FLUOROSILICATE, HYDROCHLORIC ACID)
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	8 (C1) Corrosive substances.
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Hazard identification number (Kemler code):	80
· EMS Number:	F-A,S-B
· Segregation groups	(SGG1) Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.

(Contd. on page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 10)

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

· Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

3

· Tunnel restriction code

E

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC,
N.O.S. (MAGNESIUM FLUOROSILICATE,
HYDROCHLORIC ACID), 8, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
A product information sheet can be provided if requested.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

(Contd. on page 12)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.04.2023

Version number 6 (replaces version 5)

Revision: 17.02.2022

Trade name: FloorPro Crystallising Agent RM 749

(Contd. of page 11)

H412 Harmful to aquatic life with long lasting effects.

Contact:

Regulatory Affairs

Tel.: +49-7195-14-0

productsafety.management@de.kaercher.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1: Skin corrosion/irritation – Category 1

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

0-011-871-0

749/4

2-456